



DLP™ projector
J5P Micro

Model		J5P Micro			
Reference Model		DP-2520	DP-3520	DP-6620	DP-7620
Projection System		Texas Instruments DLP™ Technology			
Panel		0.55" x 1, Type X	0.55" x 1, Type X	0.62" 720p, Type A	0.65" WXGA, Type A
Data Processor		2xLVDS DLP™ with DDP2230			
Native Resolution		SVGA 800x600	XGA 1024x768	720p	WXGA 1280x768
Brightness (Typical)	Standard mode (200W)	2000 ANSI Lumens	2000 ANSI Lumens	2000 ANSI Lumens	2000 ANSI Lumens
	Eco mode (160W)	1500 ANSI Lumens	1500 ANSI Lumens	1500 ANSI Lumens	1500 ANSI Lumens
Contrast Ratio		1800:1	1800:1	1800:1	1800:1
Brightness Uniformity (Typical)		80%	80%	80%	80%
Color Reproduction		Graphic: 24 bit 16.7M true color <UXGA, video: 27 bit 134million true color, 1080p/UXGA/WSXGA+ @ 60Hz: 16 bit 64k True Color			
Projection Lens		Manual Zoom, Manual Focus			
Digital Zoom		16x			
Zoom Ratio		1.15:1			
Focal Length		21.3 ~ 24.5mm; 2m@52"		21.3 ~ 24.5mm; 2m@59"	
Projection Distance		1.5~10m (over drive 11.5m)			
Projection Screen Size		34" ~ 260" (override to 300")		38.5" ~ 300"	
Throw Ratio (D/W)		1.9 ~ 2.2		1.5 ~ 1.8	
Optical Offset		128%	128%	136%	128%
Aspect Ratio		4:3 & 16:9			
Keystone Correction		Vertical +/- 15°			
Frequency	H-Sync	15, 21.87~91.4 KHz			
	V-Sync	43 ~ 87Hz			
Data Compatibility		VGA, SVGA, XGA, SXGA, Macintosh			
Video Compatibility		NTSC/NTSC 4.43, PAL B/G/H/I/M/N 60, SECAM, 480i/480p/720p/1080i			
Lamp Mode (Standard/Eco)		200W / 160W			
Lamp Life (Standard/Eco)		2000 hr / 3000 hr			
Acoustic Noise (Standard/Eco)		Typical: 36 / 31 dB			
Power Supply		AC input 110~240 Voltage (auto ranging)			
Power Consumption (Standard/Eco)		280W/220W			
Dimensions (WxDxH)		280x205x80 mm			
Weight (typical)		5.6 lbs			
Safety & Regulatory Compliance		FCC-B, UL/Cul, TUV, CB, CE, CCC			
Led Indicator		Power, Lamp Standby, Over Temp			
Build-in Speaker		2W mono speaker			
IO Panel	Input Terminals	VGA x 2, S-Video x 1, Composite Video x 1, Audio (RCA R&L) x 1	VGA x 2, S-Video x 1, Composite Video x 1, Audio (RCA R&L) x 1	DVI-I x 1, S-Video x 1, Composite x 1, YPbPr x 1, HDMI x 1	VGA x 2, S-Video x 1, Composite Video x 1, Audio (RCA R&L) x 1
	Output Terminals	VGA x1; Audio (mini jack) x 1		NA	VGA x1; Audio (mini jack) x 1
	Control Terminals	USB (type B) x 1; RS232 x 1			

1. All Features, specifications, model numbers are subject to change without notice.
2. Digital Light Processing and DLP are registered trademarks of Texas Instruments.



434A0612



TAIWAN

DELTA ELECTRONICS, INC.
Display Business
186, Ruey Kuang Road, Neihu, Taipei 11491,
Taiwan, R. O. C.
TEL: +886-2-8797-2088
FAX: +886-2-8797-2120

CHINA

Delta Electronics (Jiang Su) Ltd.
Visual Display Plant
1688 Jiangxing East Road,
Wujiang Economy Development Zone,
Wujiang City, Jiang Su Province, People's
Republic of China Post code: 215200
TEL: +86-512-6340-3008
FAX: +86-769-6340-7290

JAPAN

DELTA ELECTRONICS (JAPAN) INC.
Delta Shibadaimon Building
2-1-14 Shibadaimon,
Minato-Ku, Tokyo, 105-0012,
Japan
TEL : +81-3-5733-1111
FAX : +81-3-5733-1211

U.S.A.

Delta Products Corporation
15125 SW Koll Parkway, Suite K,
Beaverton, OR 97006, U.S.A.
TEL : +1-503-533-8444
FAX : +1-503-533-0204

EUROPE

DELTA ELECTRONICS (EUROPE), LTD.
Wegalaan 16
2132 JC Hoofddorp
The Netherlands
TEL: +31-23-566-8927
FAX: +31-23-566-8910

